

Model B

# SNUBNOSE Concrete Reclaimer



The Model B SNUBNOSE Reclaimer is the “workhorse” of BFK Reclaimers

Capable of reclaiming from 1/2 up to 1 yard-per-minute, the SNUBNOSE can reclaim at *twice* the rate of some competitive models, allowing your trucks to wash-out and get back under the plant as quickly as possible.

The patented design is an excellent choice for many Ready-Mix plants due to its combination of speed, simplicity, and compact size.

Available in Left- or Right-Hand Sand Screw Discharge to fit your plant. Optional Sand Screw Heater package, and Automatic Start/Stop also available.

Generally recommended for  
**Mid-to Large Size  
Ready-Mix Plants**  
Operating around  
**10-30 Mixer Trucks**

Design capacity  
**1/2 to 1 yard<sup>3</sup>-per-minute**  
[up to 0.76 m<sup>3</sup>/minute]

**2 Truck Discharge**

**Only** BFK has eliminated **Grease Fittings, Shaft Seals, and Shaker Decks**, making them the most **user-friendly** and **affordable** Reclaimers available!

**A Reclaimer so simple, you can install, operate and maintain it yourself, without the need of a factory technician!**

## The BFK Difference!

Most competitors use the “High-wear” approach to wash waste concrete.

Many designs use screws, paddle wheels or buckets to lift and drag wet concrete mix uphill thru a bath of water.

This is both slow and inefficient, leading to increased operational and maintenance costs.

BFK utilizes the effects of gravity to tumble the rock out of the mix, before the sand is rinsed and dewatered.

- Less Wear & Tear
- Less Horsepower
- Less expense
- More up-time!

That’s the BFK Difference!

**BFK TECHNOLOGIES INC.**  
CONCRETE RECLAMATION SYSTEMS



Ships Worldwide  
in (1) 20' Standard Container

**Simple, Compact, Efficient  
CONCRETE RECLAIMERS**

*Since 1997*

**Model B SNUBNOSE SPECIFICATIONS:**

- 5HP 3.7kW Submersible Pump
- 5HP 3.7kW Rotary Screen Gearmotor
- 5HP 3.7kW Sand Screw Gearmotor
- 14" 356mm Dia. Infeed Auger
- 1/4" 6mm Square Op. Rock Screen
- 24" 610mm Dia. Sand Screw
- (2) Washout Stingers

Overall Dimensions:  
12'L x 8'-6"H x 8'W [3700 x 2600x 2500mm]

Approx. Shipping Weight:  
7500# [3400kg]

Rights reserved to alter specifications without notice.  
Metric equivalents for informational purposes only.

Standard: 230/460VAC, 60Hz, 3Ø  
Optional: 380/50/3Ø or 575/60/3Ø  
Single Phase and other voltage/frequency combinations also available—Consult Factory.

