

Model M6

Concrete Reclaimer

PRECAST

Optional 2 Yard
Star Hopper

Model M6
Reclaimer

The Model M6 Reclaimer fits **so many installations never before even attempted** by other reclaimer manufacturers.

Capable of reclaiming 1 to 3 yards-per-hour, the M6 handles the small loads you need, without the price or size of a large reclaimer.

The M6 can work as a stand-alone reclaimer, or come equipped with a **wide variety of infeed hoppers, troughs, and pre-feeders** to do the job you need done!

Recommended for
**Precast, Pipe &
Block Plants**

Design capacity
1 to 3 yds³-per-hour
[up to 2.3m³/hour]

Only BFK has eliminated **Grease Fittings, Shaft Seals, and Shaker Decks**, making them the **most user-friendly and affordable** Reclaimers available!

A Reclaimer so simple, you can install, operate and maintain it yourself, without the need of a factory technician!

The BFK Difference!

Most competitors make 1 or 2 sizes of Ready-mix style reclaimers.

You can only buy what they sell, not what you truly need.

If you don't need the size or speed of a large ready-mix reclaimer, you certainly don't need the expense!

BFK offers 6 different sizes of reclaimer including the M6.

Hopper Sizes and options include:

- 1/2 to 2 Yard capacity
- Round or square
- Includes proprietary STAR Prefeeder
- Versatility by Design!
That's the BFK Difference!

BFK TECHNOLOGIES INC.
CONCRETE RECLAMATION SYSTEMS



**Simple, Compact, Efficient
CONCRETE RECLAIMERS**

Since 1997

They
Simply
Work!



Optional 2 Yard Square STAR Hopper shown.
Other sizes and styles are available.

STAR Hopper/Prefeeder generally used in precast plants, for washing out mud buckets, skid-steers, mixer trucks, etc.

Various sizes available, from 1/2" to 2 cubic yard capacity.

Handles 3/4" Max. Aggregate Size.

Consult Factory for Specifications and Shipping Weights and Dimensions.

M6 SPECIFICATIONS:

- 1.3HP 1.0kW Submersible Pump
- 3/4HP 0.6kW Rotary Screen Gearmotor
- 3/4HP 0.6kW Sand Screw Gearmotor
- 4" 100mm Dia. Infeed Auger
- 3/16" 5mm Square Op. Rock Screen
- 8" 200mm Dia. Sand Screw

Overall Dimensions:
M6 Only, assembled
5'-6"L x 5'-6"H x 6'-6"W
[1700 x 1700 x 2000mm]


Approx. Shipping Weight:
1000# [454kg]

Rights reserved to alter specifications without notice.
Metric equivalents for informational purposes only.

Standard: 230/460VAC, 60Hz, 3Ø
Optional: 380/50/3Ø or 575/60/3Ø
Single Phase and other voltage/frequency combinations also available—Consult Factory.



Optional 1/2 Yard Round STAR Hopper shown.



Optional STAR Prefeeder