



MARCO DESIGNS, BUILDS, INSTALLS, COMMISSIONS & SERVICES PORTABLE CONVEYORS FOR THE READY MIX INDUSTRY

MARCO is uniquely positioned to provide the Ready-Mix industry with a portable conveyor that optimizes both productivity and conveyor life. The **MARCO** Portable Model 521, is constructed of the components utilized in much larger solutions, but at a price and functionality targeted at the Ready-Mix market's most demanding requirements.



**O
V
E
R

70+

Y
E
A
R
S**



MODEL 521 STACKER



MODEL 521 STACKER

MODEL 521: STACKABLE CONVEYOR

Belt Width	Conveyor Length		Slope	TPH	Motor HP	Head Pulley With Bearing		Slope	TPH	Motor HP	Head Pulley With Bearing
36"	72'		14°-18°	500	20	18" Dia. 215HB		9°-13°	500	15	16" Dia. 215HB
36"	68'		14°-18°	500	20	18" Dia. 215HB		9°-13°	500	15	16" Dia. 215HB
36"	64'		14°-18°	500	20	18" Dia. 215HB		9°-13°	500	15	16" Dia. 215HB
36"	60'		14°-18°	500	20	18" Dia. 215HB		9°-13°	500	15	16" Dia. 215HB
36"	56'		14°-18°	500	20	18" Dia. 215HB		9°-13°	500	15	16" Dia. 215HB
36"	52'		14°-18°	500	20	18" Dia. 215HB		9°-13°	500	15	16" Dia. 215HB
36"	48'		14°-18°	500	15	16" Dia. 215HB		9°-13°	500	15	16" Dia. 215HB
36"	44'		14°-18°	500	15	16" Dia. 215HB		9°-13°	500	15	16" Dia. 215HB
36"	40'		14°-18°	500	15	16" Dia. 215HB		9°-13°	500	15	16" Dia. 215HB
30"	72'		14°-18°	400	15	16" Dia. 215HB		9°-13°	400	15	16" Dia. 215HB
30"	68'		14°-18°	400	20	18" Dia. 215HB		9°-13°	400	15	16" Dia. 215HB
30"	64'		14°-18°	400	15	18" Dia. 215HB		9°-13°	400	15	16" Dia. 215HB
30"	60'		14°-18°	400	15	18" Dia. 215HB		9°-13°	400	15	16" Dia. 215HB
30"	56'		14°-18°	400	15	16" Dia. 215HB		9°-13°	400	10	16" Dia. 215HB
30"	52'		14°-18°	400	15	16" Dia. 215HB		9°-13°	400	10	16" Dia. 207SB
30"	48'		14°-18°	400	15	16" Dia. 215HB		9°-13°	400	10	16" Dia. 207SB
30"	44'		14°-18°	400	15	16" Dia. 215HB		9°-13°	400	10	16" Dia. 207SB
30"	40'		14°-18°	400	15	16" Dia. 215HB		9°-13°	400	10	16" Dia. 207SB
24"	72'		14°-18°	300	15	16" Dia. 215HB		9°-13°	300	10	16" Dia. 207SB
24"	68'		14°-18°	300	15	16" Dia. 215HB		9°-13°	300	10	16" Dia. 207SB
24"	64'		14°-18°	300	15	16" Dia. 215HB		9°-13°	300	10	16" Dia. 207SB
24"	60'		14°-18°	300	15	16" Dia. 215HB		9°-13°	300	10	16" Dia. 215HB
24"	56'		14°-18°	300	10	16" Dia. 207SB		9°-13°	300	7.5	16" Dia. 207SB
24"	52'		14°-18°	300	10	16" Dia. 207SB		9°-13°	300	7.5	16" Dia. 207SB
24"	48'		14°-18°	300	10	16" Dia. 207SB		9°-13°	300	7.5	16" Dia. 207SB
24"	44'		14°-18°	300	10	16" Dia. 207SB		9°-13°	300	7.5	16" Dia. 207SB
24"	40'		14°-18°	300	10	16" Dia. 207SB		9°-13°	300	7.5	16" Dia. 207SB

NOTE: ALL MODEL 521 CONVEYORS ARE: 400 FPM, TAIL PULLEY OF 14" DIA. WITH 207SB

STANDARD FEATURES:

- Head Pulley with Vulcanized Lagging XT Hubs and Bushings
- Tail Pulley (Self Cleaning) with XT Hubs and Bushings
- Reducer - Class II
- Idlers - Sealed Bearing CEMA B5 Carrier and Return
- Conveyor Belt - 2 Ply (Spliced)
- MARCO Paint System (Gray, Green or White)

STANDARD FEATURES: (CONT)

- Motor - 1800 RPM T.E.F.C..230/460 Volt
- "Rock Box" Type Loading Hopper

OPTIONAL FEATURES:

- Confining Chute (No Head Guard Required).
- Conveyor Supports
- Idlers - Sealed CEMA C5 Carrier and Return
- Belt Wiper
- Conveyor Belt - 3 Ply (Spliced or Vulcanized)