

COUGAR® TRUCK VIBRATORS

MOBILE VIBRATION SOLUTIONS

L3608



THE MOST RUGGED, RELIABLE TRUCK VIBRATORS ON THE MARKET.

Cougar® Vibrators • The pioneer in truck vibrators since 1964.





ENGINEERED VIBRATION

Adding a Cougar® Truck Vibrator not only saves you money on costly repairs to your trucks, it increases productivity by eliminating carryback. Cougar® Truck Vibrators give you more payload per cycle and fewer cycles per job. Fewer cycles give you lower labor and fuel costs and decrease vehicle wear. Material is evenly distributed during spreading. Cougar® Truck Vibrators eliminate bed cleanout time and the need for workers to climb into the truck beds to manually remove material, resulting in lower workman compensation claims.

- Easy, low-cost installation
- Shielded, oversized, permanently-lubricated ball bearings that assure exceptional service life
- · Sealed against dirt, dust, and water for long life in extreme conditions
- Small size and light weight with high-speed, low-amp electric motors

THE PIONEER IN TRUCK VIBRATORS

Cougar Vibration patented the world's first 12-volt truck vibrator in 1964 and has steadfastly remained focused on industrial vibration. Cougar has since become a name synonymous with exceptional quality products, workmanship and service support.

Martin Engineering purchased Cougar in 2010 making Martin the world's leader in industrial vibration. Established in 1944, Martin is the leading international developer, manufacturer and supplier of innovations to make the handling of bulk materials cleaner, safer and more productive.



ELECTRICS

PAGE 6





12/24 volt DC vibrators ideal for:

- · Dump trucks
- · Mounted spreaders
- Sanitation, pumper and vacuum trucks



DC1-400

12/24 volt DC vibrator ideal for:

Concrete pumpers



DC-200/-80

12 volt DC vibrators ideal for:

- · ATV or tailgate spreaders
- · Mixer truck charge chutes

HYDRAULICS & PNEUMATICS

PAGE 8



NHD-110

Hydraulic vibrator ideal for:



5016

Pneumatic piston vibrator ideal for:



ATU-43

Pneumatic turbine vibrator ideal for:





ELECTRICS

DC-3200/-2500/-1100, DC1-400 & DC-200/-80







DC-3200

DC1-400

DC-80

A complete line of rugged, durable truck vibrators, Cougar® 12/24 Volt DC Mobile Vibrators improve the speed and control of material flow from dump trucks and other self-powered heavy equipment.

Shielded, oversized, permanently-lubricated ball bearings assure exceptional service life.

Sealed against dirt, dust, and water for long life in extreme conditions.

Small size and light weight with highspeed, low-amp electric motors.

Easy, low-cost installation.





HYDRAULICS & PNEUMATICS

NHD-110, 5016 & ATU-43



NHD-110 / HYDRAULIC POWER / ROTATIONAL FORCE

Strong ductile iron for maximum durability in continuousduty applications. Requires minimal maintenance.

Efficient motor designed for minimal power consumption with low noise output.



5016 / PNEUMATIC POWER / LINEAR FORCE

Options include: Air-cushioned, nonimpacting action

Internal spring for positive starting Universal mount

Manifold/muffler for quiet operation



ATU-43 / PNEUMATIC POWER / ROTATIONAL FORCE

Optional speed muffler allows precision control of force and speed (regular muffler comes standard).

Lower air consumption than comparable air vibrator.

Low 62-78 dBA noise level is well below OSHA standards.

Excellent power to weight ratio with a 350°F temperature rating.

Durable anodized aluminum finish provides a tough exterior (paint optional).


No lubrication required.




ACCESSORIES & SPECIFICATIONS

Ac	cessory F	Parts		Applicable Vibrator Models							
Description	1	Part #	DC-80	DC-200	DC-1100	DC-2500	DC-3200	DC1-400	NHD-110		
Timer 12 Volt 45 secs on, 90 secs off		197266	Х	X	Х	×	X	X			
Timer 12 Vo 5 secs on, resets af		197266-01	Х	X	Х	×	X	X			
Timer 12/24 Volt 1-100 secs on, 1-100 secs off		197265	Х	X	×	×	×	Х			
Circuit	12 Volt	193215			Х	Х	X	X			
Breaker	24 Volt	193218			Х	Х	Х	X			
	12 Volt	221615						X			
	24 Volt	221616						X			
	12 Volt	221611			X	X		X X X X X X X X X X X X X X X X X X X			
	24 Volt	221624			X	X					
.	12 Volt	221625					X				
Truck Mount Kit	24 Volt	221623					X				
	12 Volt Aluminum	221617			×	×					
	12 Volt Aluminum	221618					×				
	12 Volt	221614						X			
	24 Volt	221619						X			
		220505						X			
Mount Dista		220491-01	X	X							
Mount Plate	5	220525			X	X					
		220526					X		X		
Aluminum		220581			X	Х					
Mount Plate	s	220582					X		X		
Control Kit		196854-01	X	X							
Trailer	Plug	194996			X	X	X				
Connector	Socket	194997			Χ	X	X	X X X			
Truck Cable		195103			X	Х	X				
(Must specify length)	195109						X			







Hydraulic '	(inches)	Bolt	Pattern	Bolt Size	Port	Weight		
Model	Α	В	С	D	E	F	G	(lbs)
NHD-110	7 1/2	10	8 5/8	2	8	5/8	3/4-16 SAE	37





12/24 Volt DC Performance										
Model	In. Lbs	VPM	Force Lbs	Amps (12V)	Amps (24V)					
DC-3200	7.00	4000	3200	85	62					
DC-2500	3.50	5000	2500	72	55					
DC-1100	1.50	5000	1000	70	55					
DC1-400	1.00	3800	410	15	7					
DC-200	0.36	4500	200	5	-					
DC-80	0.18	4000	80	5	-					





12/24 Volt	DC Dimen	sions (inch	ies)	Bolt	Pattern	Bolt Size	Weight	
Model	Α	В	С	D	Е	F	(lbs)	
DC-3200	10 3/8	9 3/4	6 7/8	2	8	5/8 x 1 3/4	36	
DC-2500	10	9 3/4	6 7/8	1	8	5/8 x 1 3/4	31	
DC-1100	10	9 3/4	6 7/8	ı	8	5/8 x 1 3/4	30	
DC1-400	9 1/16	6 3/8	5 9/16	3 3/4	5	3/8 x 1 1/2	18	
DC-200	5 11/16	5	3 7/16	2	4	3/8 x 1 1/4	5	
DC-80	5 11/16	5	3 7/16	2	4	3/8 x 1 1/4	5	





Pneumatic Vibrator Air Performance										
Model	Piston	40	PSI	60 PSI		Max 80 PSI				
	Size	VPM	CFM	VPM	CFM	VPM	CFM			
5016	2	2600	11	3900	16.1	4100	20.9			
ATU-43	-	ı	-	11700	9.4	13000	11.7			

Pneumatic Vibrator Dimensions (inches)										
Model	Piston	A	В	C	Bolt	Bolt Size	Port NPT	Weight		
	Size				D	F	G	(lbs)		
5016	2	7 1/2	3 1/2	7	6	5/8	1/4	20		
ATU-43	-	5 3/4	2 1/4	3 5/32	4	3/8	1/4	3		

