


T2P1 Tension Canister, Alloy Steel



Picture is a representation of actual product



SPECIFICATIONS

Full Scale Output: 2.0 mV/V	Seal Type: Environmentally sealed	Insulation Resistance: 5000 megohms	Cable Color Code: Green + Excitation Black - Excitation White + Signal Red - Signal Yellow - Shield
Output Resistance: 350 ohms +/- 3.5	Safe Overload: 150% Full scale	Deflection at Capacity: 20,000 lb=.0075 in/.191 mm, 50,000 lb=.0100 in/.254 mm	Warranty: One-year limited warranty
Input Resistance: 350 ohms +/- 3.5	Rated Excitation: 10V AC/DC (20V maximum)	Cable Length: 35 ft/10.7 m	Approvals:
Material/Finish: High-alloy steel, epoxy coated	Combined Error: ±0.03% Full scale		
Temperature: Compensated range 0°F to 150°F/-17°C to 65°C	Repeatability: 0.02% Full scale		

DIMENSIONS

RATED CAPACITY	A	B	C	D	*E	F	G	H	I	J	K	L	M
lb/inches													
20,000	8.50	2.63	2.75	.50	1.00	3.38	1.38	1.81	1.00	5.81	4.00	5.00	1 1/2-12 UNF-2B x 2 DP
50,000	11.44	3.75	4.00	.63	1.00	5.00	1.38	1.81	1.00	5.81	5.75	6.50	2-12 UNF-2B x 2.63 DP
kg/mm													
9071.9	215.9	66.8	69.9	12.7	25.4	85.9	35.1	46.0	25.4	147.6	101.6	127.0	1 1/2-12 UNF-2B x 50.8 DP
22,679.7	290.6	95.3	101.6	16.0	25.4	127.0	35.1	46.0	25.4	147.6	146.1	165.1	2-12 UNF-2B x 66.7 DP

ORDER INFORMATION

LOAD RATING	PART #	PRICE
20,000 lb (9071.9 kg)	17660	Consult
50,000 lb (22,679.6 kg)	17661	Consult

INTERCHANGEABLE PRODUCTS

MANUFACTURER	MODEL
Fairbanks®	657090, 657091
Streeter Richardson	2011711, 2011712

VPG - BLH

