

Inlet Vacuum Filters

"CSL" Series 3" - 6" MPT

APPLICATIONS & EQUIPMENT

- Vacuum Pumps & Systems P.D., Side Channel, Rotary Vane, Screw, Piston
- Vacuum Packaging Equipment
- Vacuum Furnaces
- Blowers Side Channel & P.D.
- Intake Suction Filters

- Pneumatic Conveying Systems
- Remote Install for Piston, Screw
 & Centrifugal Compressors
- Factory Automation Equip
- Ash Handling
- Food Industry
- Paper Processing
- Glass, Ceramic ProcessingWaste Water Treatment
- Woodworking
- Cement
- · Bag House Systems
- Envelope Manufacturing
- Medical Industry
- · Chemical Processing

FEATURES & SPECIFICATIONS

- Vacuum level: Typically 1x10⁻³ mmHg (1.3x10⁻³ mbar)
- Polyester: 99%+ removal efficiency standard to 5 micron
- Paper: 99%+ removal efficiency standard to 2 micron
- Heavy duty T bolts for easy maintenance
- Hydrostatically tested to 0.5 bar pressure for vacuum tightness
- Low pressure drop
- · Positive engagement O-ring seal system

- Large dirt holding capacity and Easy field cleaning, especially when mounted horizontally or inverted
- Inlet/outlet 1/4" gauge taps standard
- Rugged all steel construction w/baked enamel finish
- Temp (continuous): min -15°F (-26°C) 220°F (max 104°C)
- Filter change out differential: 10" 15" H₂O over initial delta P
- Pressure drop graphs available upon request

OPTIONS (Inquiries Encouraged)


- · Various media
- Larger sizes available
- Straight-Through Configurations
- Available in Stainless Steel
- Epoxy coated housings
- · Support brackets

- · Special connections
- Activated carbon prefilters to reduce order

CONFIGURATION

DRAWING





Dimension tolerance + 1/4"

I = Industrial Duty S = Severe Duty E = Extreme Duty

	н.											
	П	with	with	MPT	_					Rated Flow SCFM		
	V	Polyester	ster Paper Inlet & DIMENSIONS - inches					Nominal	Element	Approx.		
	'	Element	Element	Outlet	Α	В	С	D	Е	Rating	Rating	Wt. lbs
Γ	I	CSL-235P-300	CSL-234P-300	3"	27 1/8	9	14	18 1/2	10	300	570	47
	S	CSL-335P-300	CSL-334P-300	3"	27 1/8	9	14	18 1/2	15	300	800	50
	Ι	CSL-235P-400	CSL-234P-400	4"	27 1/8	9	14	18 1/2	10	520	570	52
	S	CSL-335P-400	CSL-334P-400	4"	27 1/8	9	14	18 1/2	15	520	800	55
ı	I	CSL-245P-500	CSL-244P-500	5"	28 1/8	11	18 1/2	19 1/2	10	800	880	82
	S	CSL-345P-500	CSL-344P-500	5"	28 1/8	11	18 1/2	19 1/2	15	800	1100	88
	Ι	CSL-275P-600	CSL-274P-600	6"	29 1/8	12	18 1/2	20 1/2	10	1100	1100	95
	S	CSL-375P-600	CSL-374P-600	6"	29 1/8	12	18 1/2	20 1/2	15	1100	1500	97

