

POWER ON BOARD. YOU CAN COUNT ON IT. THE CS 31 BATTERY OPERATED DIGITAL INDICATOR FROM FIRST-WEIGH.

Has a full
function
numeric
keyboard



Operates
on 8 D-Cell
Batteries.
Operates
4000 Hours
between Battery
Changes.

**Designed for portable remote locations, rentals and
counting applications.
Use it as an Indicator or as a Counting Scale.**

Standard Features:

- | | | |
|---|---------------------------------|---|
| 1. Counting Feature. | 4. Great for Portable Scale. | 8. Remote Locations where
A/C Voltage is not available. |
| 2. Stainless Steel
NEMA 4 Enclosure. | 5. Count In or Count Out. | 9. Numeric - Tare, Average Piece
Weight Entry. and Sample. |
| 3. 16 Dual Function Keys. | 6. Power is 8 D-Cell Batteries. | |
| | 7. Lb/Kg Selectable. | |

Optional: Input from 2nd Scale Platform.



Jamieson Equipment Company
www.jamiesonequipment.com
toll free 800.875.0280

SPECIFICATIONS / STANDARD FEATURES

FIRST-WEIGH MODEL CS 31 BATTERY OPERATED DIGITAL INDICATOR

- 1 **Displays** - Dual 1/2" LCD Weight and Piece Count - 6 Digits each.
- 2 **Counting Function** - with Sample or APW Entry Plus Accumulated Count with Total.
- 3 **Key Functions** - 0 thru 9, <TARE>, <APW>, <SAMPLE>, <FUNCTION>, <GROSS/NET>, <LB/KG>, <ADD>, <TOTAL>, <CLEAR TOTAL>, <ZERO>, <COUNT OUT> and Optional Scale Select - Integral Tactile - Feel Membrane Keyboard Switches.
- 4 **Displayed Resolution:** 1 - 5,000 Displayed Graduation
1 - 999,999 Piece Count Display
- 5 **Load Cell Excitation** - Drives up to four 350-ohm Load Cells.
- 6 **Decimal** - 0-3 Programmable.
- 7 **Mount** - S.S. Universal - Desk/Wall Mount.
- 8 **Calibration** - Via Keyboard with Internal Protection Switch.
- 9 **Load Cell Connector** - 7 Pin Connector - Waterproof.
- 10 **Power Input** - 8 D-Cell Batteries. Up to 4000 Hours of Continuous Use on Single Cell Applications.
- 11 **Physical Dimensions** - Height 6 1/2", Width 10", Depth 5 1/2". Overall height with Universal Stand, 9".
- 12 **RFI/EM Shielding** - Meets NIST H-44 Guidelines.
- 13 **Operating Temperature** - 10° C (17° F) to +40° (122° F).



OPTIONAL: 2nd Scale Input for 2 Scale Weighing and Counting

POWER ON BOARD