

Model X2

# SIX-SHOOTER Concrete Reclaimer



The Model X2 Double-Wide SIX-SHOOTER Reclaimer is ideal for plants with lesser amounts of daily waste concrete, but still need the ability to wash-out 2 mixer trucks at once.

The Model X2 SIX-SHOOTER is capable of reclaiming from 1/4 to 1/2 yard-per-minute, making it as fast as many competitors largest machines!

Make sure to compare thru-put and No. of Truck capabilities when comparing to competitive brands!

Available in Left- or Right—Hand Sand Screw Discharge to fit your plant. Optional Sand Screw Heater package, and Automatic Start/Stop also available.

Generally recommended for  
**Small to Mid-Size  
Ready-Mix Plants**

Operating around  
**3 to 10 Mixer Trucks**

Design capacity  
**1/4 to 1/2 yard<sup>3</sup>-per-minute**  
[up to 0.38 m<sup>3</sup>/minute]

**2 Truck Discharge.**

*Only* BFK has eliminated **Grease Fittings, Shaft Seals, and Shaker Decks**, making them the most user-friendly and affordable Reclaimers available!

A Reclaimer so simple, you can install, operate and maintain it yourself, without the need of a factory technician!

## The BFK Difference!

The X2 is a versatile system, fitting the bill for the smaller producers, while increasing traffic flow at the reclaimer.

A “Double-Wide” version of the Model X1, the X2 allows 2 trucks to simultaneously wash out.

And the X2 offers the same design features and benefits you’ve come to expect from a BFK: not just another screw, paddle wheel, or bucket reclaimer!

- Less Wear & Tear
  - Less Horsepower
  - Less expense
  - More up-time!
- That’s the BFK Difference!

**BFK TECHNOLOGIES INC.**  
CONCRETE RECLAMATION SYSTEMS



**Simple, Compact, Efficient  
CONCRETE RECLAIMERS**

*Since 1997*

**X2 SIX-SHOOTER SPECIFICATIONS:**

- 5HP 3.7kW Submersible Pump
- 3HP 2.2kW Rotary Screen Gearmotor
- 3HP 2.2kW Sand Screw Gearmotor
- 8" 200mm Dia. Infeed Auger
- 1/4" 6mm Square Op. Rock Screen
- 12" 305mm Dia. Sand Screw
- (2) Washout Stingers

**Overall Dimensions:**  
10'-6" L x 6'H x 8'W  
[3200 x 1800 x 2400mm]

**Approx. Shipping Weight:**  
5400# [2450kg]

Standard: 230/460VAC, 60Hz, 3ø  
Optional: 380/50/3ø or 575/60/3ø  
Single Phase and other voltage/frequency  
combinations also available—Consult Factory.

Rights reserved to alter specifications without notice.  
Metric equivalents for informational purposes only.

Ships Worldwide in (1) 20' Standard Container

- ONE Screen
- ONE Screw
- ONE Pump
- ...only 11  
Horsepower

They  
Simply  
Work!

