

Battery Charger

Remtron™ 411, 611, Pump Boss™ and Safe-D-Stop™



HIGHLIGHTS

- Drop transmitter into the charger to begin charging
- Battery removal is not required
- Three-hour charge time
- Fully automatic charging
- Charge status LED
- Power adapters for various countries
- Desk mount is standard
- Wall mount adapter option

TECHNICAL DATA AND SPECIFICATIONS

SPECIFICATIONS	
Weight	< 0.5kg (1lb)
Dimensions (W x H x D)	145 x 117 x 95 mm (5.7 X 4.6 X 3.7 inches)
Supply Voltage	Various DC and AC to suit most applications and countries
Supply Current	< 2A
Charging Temperature	10C to 45C (50F to 113F)
Storage Temperature	-20C to +60°C (-4F to 140F)
Standards	IEC61010, EN301489
Protection Class	IP44 (indoor)
Adapter Part Number	2OPT-9231-A001
Wall Mount Part Number	PRT-0002453

CUSTOMS DATA	
Country of origin	United States of America

North America: +1.234.806.0018 | Sales.US@Cattron.com

Europe: +49.2151.4795.0 | Sales.EU@Cattron.com

UK: +44.1932.238121 | Sales.UK@Cattron.com

South America: +55.19.3518.7030 | Sales.BR@Cattron.com

Asia: Sales.CN@Cattron.com

Oceania: Sales.AU@Cattron.com

cattron.com

EN-2024-10-V4

Cattron™ reserves the right to change specifications and product details on this datasheet without prior notice. Cattron and all associated logos or marks are trademarks of Cattron and/or its subsidiaries. All rights reserved.