

# **Compact Exposed Element Filters**

"FT" Series 3" - 6" MPT

#### **APPLICATIONS & EQUIPMENT**

- · Industrial & Severe Duty
- · Piston Compressors
- Screw Compressors
- Blowers Side Channel & P.D.
- Hydraulic Breathers fine filtration
- Engines
- Fans
- Construction
- Medical
- Pneumatic Conveying
- Waste Water Aeration
- Sparging
- Power Plants
- Factory Air

## **FEATURES & SPECIFICATIONS**

- Polyester: 99%+ removal efficiency standard to 5 micron
- Paper: 99%+ removal efficiency standard to 2 micron
- Exposed element for optimal air flow and low restriction
- Center bracket located for minimal flow restriction
- Heavy gauge base with low pressure drop outlet pipe design
- Durable carbon steel construction with baked enamel finish
- Interchangeable media: Polyester, Paper, HEPA
- Several element sizes available at a given connection size providing a choice according to severity of your application
- Temp (continuous): min -15°F (-26°C) max 220°F (104°C)
- Filter change out differential: 10"-15" H<sub>2</sub>O over initial delta P
- · Pressure drop graphs available upon request


#### **OPTIONS** (Inquiries Encouraged)

- 1/8" tap holes
- · Pressure Drop Indicator
- Available in Stainless Steel
- · Epoxy coated housings
- · Various media available
- · Special connections, BSPT

### **CONFIGURATION**



#### **DRAWING**



Dimension tolerance + 1/4"

## I = Industrial Duty S = Severe Duty E = Extreme Duty

1							Rated Flow SCFM			
	with	with		DIMENSIONS - inches			Screw,			
,	Polyester	Paper	MPT					Blower,	Element	Approx.
	Element	Element	Outlet	Α	В	С	Piston	Fan	Rating	Wt. lbs
S	FT-235P-300	FT-234P-300	3"	13	3	8	300	300	570	13
S	FT-245P-300	FT-244P-300	3"	13	3	10	300	300	880	19
Е	FT-275P-300	FT-274P-300	3"	13	3	12	300	300	1100	22
I	FT-235P-400	FT-234P-400	4"	14	4	8	300	520	570	17
S	FT-245P-400	FT-244P-400	4"	14	4	10	450	520	880	20
Е	FT-275P-400	FT-274P-400	4"	14	4	12	450	520	1100	24
I	FT-245P-500	FT-244P-500	5"	14	4	10	500	800	880	21
S	FT-275P-500	FT-274P-500	5"	14	4	12	650	800	1100	25
I	FT-275P-600	FT-274P-600	6"	15	5	12	650	1100	1100	27

