

Model 60040

Vishay Sensortronics

Low Profile Bending Beam



actory Mutual ystem pproved

FEATURES

- · Rated capacities of 25 to 500 pounds
- · Tension or compression loading capabilities
- · Compact, low profile design
- Sensorgage[™] sealed to IP65 standards
- Factory Mutual System Approved for Classes I, II, III; Divisions 1 and 2; Groups A through G. Also, non-incendive ratings (No barriers!).

OPTIONAL FEATURE

Companion tank weighing assemblies available (65059 TWA)

DESCRIPTION

The 60040 is a compact, low capacity, alloy-steel, high-precision bending-beam load cell.

This product's small size and accuracy makes it ideal for applications that demand high performance from a small package. This load cell is commonly used in platform scales, conveyer scales, and varied process weighing applications. This product is rated intrinsically safe by the Factory Mutual System (FM); making it suitable for use in potentially explosive environments. It is also available with mounting accessories under Weighing Assembly Model 65059.

- Output

White

APPLICATIONS

- Bin and hopper weighing
- · Belt conveyor scales
- Netweighing

OUTLINE DIMENSIONS in inches





Model 60040

Vishay Sensortronics

Low Profile Bending Beam



SPECIFICATIONS

PARAMETER	VALUE	UNIT
Rated capacity-R.C. (E _{max})	25, 50, 100, 150, 250, 500	lbs
NTEP/OIML Accuracy class	Standard	
Maximum no. of intervals (n)		
Rated output-R.O.	2.0	mV/V
Rated output tolerance	+0.2510	±% mV/V
Zero balance	1.0	±% FSO
Combined error	0.03	±% FSO
Non-repeatability	0.01	±% FSO
Creep error (20 minutes)	0.03	±% FSO
Temperature effect on zero	0.0015	±% FSO/°F
Temperature effect on output	0.0008	±% of load/°F
Compensated temperature range	14 to 104 (-10 to 40)	°F (°C)
Operating temperature range	0 to 150 (-18 to 65)	°F (°C)
Storage temperature range	-60 to 185 (-50 to 85)	°F (°C)
Maximum safe central overload	150	% of R.C.
Ultimate central overload	300	% of R.C.
Excitation, recommended	10	Vdc or Vac rms
Excitation, maximum	15	Vdc or Vac rms
Input impedance	380 - 450	Ω
Output impedance	349 - 355	Ω
Insulation resistance at 50VDC	>1000	MΩ
Material	Nickel plated alloy steel	
Environmental protection	IP65	

FSO - Full Scale Output

All specifications subject to change without notice.





Vishay

Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.

