

TRANSPORT™

TRANSPORT™ CC LOCOMOTIVE REMOTE CONTROL



HIGHLIGHTS

- Cruise control enables operators to set a fixed speed
- Compact, single cabinet, cab mounted design reduces space requirements
- Designed to streamline and simplify product installation and maintenance
- Self-monitoring system ensures OCU and LCU are fully operational
- Configurable to customer requirements

FEATURES

- Configurable speed selection lever, up to eight-speed steps
- Directional control
- Independent brake control
- Train brake control
- Bell and horn
- Sand control
- Bail control
- Emergency brake
- Vigilance or PTO protection
- Tilt detection
- Headlight control: off, dim, bright
- Heated LCU cabinet

OPTIONS

- Talkback two-way communication
- Repeaters when an extended range is required
- Tilt time extend
- Man-down alert
- External emergency stop switches
- External status lights





TECHNICAL DATA AND SPECIFICATIONS

MECHANICAL DATA	
Supply Voltage	32 VDC or 64 VDC
Frequency Range	UHF: 450 – 470 MHz
RF Range	One mile line of sight
Internal Archive Record	32 MB FIFO
Temperature	-30° to +65° C / -22° to +150°F RH 0 to 95% non-condensing

OPERATOR CONTROL UNITS	
Compatible OCUs	Transport OCU
	Toggle OCU
	Paddle OCU
	A0-Series OCU

North America: +1.234.806.0018 | Sales.US@Cattron.com
Europe: +49.2151.4795.0 | Sales.EU@Cattron.com
UK: +44.1932.238121 | Sales.UK@Cattron.com
South America: +55.19.3518.7030 | Sales.BR@Cattron.com
Asia: Sales.CN@Cattron.com
Oceania: Sales.AU@Cattron.com

cattron.com

EN-2024-06-V6

Cattron™ reserves the right to change specifications and product details on this datasheet without prior notice. Cattron and all associated logos or marks are trademarks of Cattron and/or its subsidiaries. All rights reserved.

