## VIBCO® Vibrators

## Reversible Plate Compactors

Model VR-20®

"No more dragging, pulling or pushing your plate compactors . . ."



Swing-over handle locks in forward or straight up

VR-20 with a 20" x 19" plate is the true brute in the reversible plate compactor field. VIBCO guarantees customer satisfaction on all of our plate compactors.

Customers' comments include: "It makes working in tight spaces easy. This reversible compactor allows you to get into the tightest corners and with a flip of a lever, easily backs up." It's 6.5 hp HONDA engine and 4,350 lbs. of impact force indicates the available power. A water tank kit for asphalt

compaction can easily be added to all VR compactors.

## SPECIFICATIONS VR-20

PLATE SIZE Inch	20 x 19	
mm	508 x 483 mm	
WEIGHT Lbs	311 lbs.	
Kg	141 kg.	
CENTRIFUGAL FORCE	4350 Lbs.	
A TO COMPANY STATE OF THE PARTY	20000 N*	
VIBRATION FREQUENCY	3850 VPM	

\*N = Centrifugal Force in Newton

ENGINE SPEED		3400 RPM
TRAVEL SPEED	Forward	65 ft./min.
	Reverse	65 ft./min.
ENGINE	Honda	6.5hp
SPECIFIC CENTRIFUGAL FORCE		11.7 PSI
SPECIFIC CENTRIFUGAL FORCE		11.7 PSI



## **Reversible Plate Compactors**



Heavy duty unitized self-cleaning base plate with rounded sides to avoid "dig-down"

No more dragging, pulling or pushing. The VR-18® (18" wide) and VR-12® (12" wide) reversible plate compactors will solve your problems compacting asphalt or dirt in ditches, inside foundations or any tight spot.



SPECIFICATIONS	VR-12	VR-18
PLATE SIZE Inch	12 x 20-1/2	18 x 24
	305 x 520 mm	458 x 610 mm
WEIGHT Ibs	130 lbs.	160 lbs.
kg	59 kg.	73 kg.
CENTRIFUGAL FORCE	2000 lbs.	3000 lbs.
	8900 N*	13350 N*
VIBRATION FREQUENCY	5000 VPM	5000 VPM
ENGINE SPEED	3000 RPM	3000 RPM
Forward TRAVEL SPEED Reverse	75 ft/min	85 ft/min
	23m/min	26 m/min
	70 ft/min	75 ft/min
	21 m/min	23 m/min
ENGINE Honda	3 hp	4 hp
SPECIFIC CENTRIFUGAL FORCE	10.2 psi	10.7 psi

\*N = Centrifugal Force in Newton

VIBCO, INC.

