



INDUSTRIAL GRADE SPEED REDUCERS

If you run a pumping, lifting, crushing, harvesting, processing, manufacturing or distribution operation, WorldWide Electric has the right speed reducers to keep you running smoothly, day-in and day-out. All of our industrial grade speed reducers are in stock with immediate shipping available, whether that's a large size 10 shaft mount reducer, or the smallest of right angle worm gear speed reducers.

SHAFT MOUNT REDUCERS

WorldWide Electric's Shaft Mount Reducers are dimensional equivalents to the popular TXT Series, allowing them to accept all TXT compatible accessories.

THE "ULTIMATE" Shaft Mount Reducer

- Box sizes 2-9
- Speed ratios 9:1, 15:1 and 25:1
- Handles 1-1/4" to 4-15/16" shaft sizes
- Heavy duty FCD45 cast iron housing
- A.G.M.A. rated Class 11 hardened gears
- Tapped to accept scw conveyor accessories on sizes 2-6
- Torque arm included
- Three-year warranty



THE "ORIGINAL" Shaft Mount Reducer

- Box sizes 2-10
- Speed ratios 15:1 and 25:1
- Handles 1-1/4" to 5-7/16" shaft sizes
- Torque arm included
- Two-year warranty



Maximize Your Savings
Use our industry grade accessories designed to fit TXT compatible series shaft mount reducers.


Motor Mounts



Tapered Bushing Kits



Belt Guards



Backstop Assemblies *



* Suitable for use in WWWE shaft mount reducers only.

Screw Conveyor Flanges (SCF)




Screw Conveyor Drive Shafts (SCDS)



ACCESSORIES

DRIVING & CONTROLLING

INDUSTRY



INLINE HELICAL SPEED REDUCER

WorldWide Electric's Inline Helical Speed Reducers offer physical specifications to match the "R" Series of the inline market leader - making it a drop in replacement. It's broad range of power and output torque options support a wide range of tough applications.



THE "WINL" SERIES Inline Helical Speed Reducer

- 1/4-100 HP; Box sizes 37-147
- Speed ratios 2:1 - 120:1
- Output torques to 83,300 lb-in
- Cast iron housing
- Precision processed gears
- Two-year warranty

WORM GEAR REDUCERS

WorldWide Electric's Right Angle Worm Gear Reducers offer a high quality replacement for existing Boston 700 Series or Motovario NMRV Series gearboxes, and are readily available in all input and output configurations.

Flange Input
Shaft Output (Double)



Flange Input
Shaft Output (Right)



Flange Input
Shaft Output (Left)



"HDR" SERIES



Flange Input
Hollow Bore Output



Shaft Input
Shaft Output (Right)

Shaft Input
Shaft Output (Left)



"CALM" SERIES
Flange Input
Hollow Bore Output
(Shaft Output Available)

THE "HDR" SERIES Heavy Duty - Cast Iron

- 56C, 145TC and 182/4TC compatible
- Center distances from 1.33" to 3.25"
- Speed ratios ranging from 5:1 to 60:1
- Pre-filled with premium synthetic oil (Mobil SHC634)
- Flange and shaft input options

THE "CALM" SERIES Lightweight - Aluminum

- 56C, 145TC and 182/4TC compatible
- NEMA motor input flanges
- Box sizes from 30 to 90 mm
- Speed ratios ranging from 7.5:1 to 100:1
- Pre-filled with premium synthetic oil (Mobil SHC634)